

Article

Multivariate Statistical Approach to Study Spatiotemporal Variations in Water Quality of aHimalayan Urban Fresh Water Lake

Tawseef Ahmad ¹, Gaganjot Gupta ¹, Anshula Sharma ¹, Baljinder Kaur ^{1,*}, Abdulaziz Abdullah Alsahli ² and Parvaiz Ahmad ^{2,3,*}

- ¹ Department of Biotechnology, Punjabi University Patiala, Patiala 147002, India; tawseef.672@gmail.com (T.A.); gaganbt01@gmail.com (G.G.); anshula2sharma@gmail.com (A.S.)
- ² Botany and Microbiology Department, Faculty of Science, King Saud University, Riyadh 11451, Saudi Arabia; aalshenaifi@ksu.edu.sa
- ³ Department of Botany, Sri Pratap College, Srinagar 190001, Jammu and Kashmir, India
- * Correspondence: baljinderkaur@pbi.ac.in (B.K.); parvaizbot@yahoo.com (P.A.)

Received: 18 July 2020; Accepted: 18 August 2020; Published: 24 August 2020



Abstract: Physicochemical parameters determining Dal Lake water quality were evaluated at four different sites during 2016–2017 in four different seasons Spring (April), Summer (July), Autumn (October), and Winter (January). The observed physicochemical values were analyzed by statistical (discriminant analysis) and arithmetic (WQI) methods to ascertain sources and levels of pollution. Discriminant analysis helped to access the contribution of each physicochemical parameter in water quality in the context of sampling sites (spatial) and seasons (temporal) to discriminate pollution loading between sites and as well as seasons. Factors such as temperature, alkalinity, ammoniacal nitrogen, total phosphorous, and orthophosphorous exhibited a strong contribution in the discrimination of sampling sites, while factors such as temperature, alkalinity, hardness, BOD, nitrate nitrogen, and total phosphorous exhibited a strong contribution in the discrimination of sampling sites for four sampling sites were calculated and indicated that the water at Site I was the most contaminated followed by Site IV, while Site III was the least contaminated. Thus, highlighting that the pressure of anthropogenic activities is subjecting Dal Lake to an unnatural death.

Keywords: physicochemical parameters; Dal Lake; discriminant analysis; water quality index; seasons; sites

1. Introduction

Dal Lake—known as the 'Jewel of Kashmir' is one of the most attractive tourist destinations in the world. The lake is surrounded by mountains on its three sides, Zabarwan in the east, Kohimaraan in the west, and Shankacharya in the south and is adjoined by beautiful Mughal gardens [1]. It is well known for its tourism and economic potential, as a multi-basin lake, covering an area of 16.6 km² and with a water holding capacity of 15.45×10^6 m³ [2]. Dal Lake has evolved as eutrophic in nature because of the discharge of organic rich effluents, sewage, sediments, and other nutrients from the surroundings and the floating gardens established within it. Several anthropogenic activities and ecological stress have forced the lake to shrink like other cases of the world, such as the Aral Sea [3] and the Dead Sea [4], in terms of its surface area, water quality as well as the nature of biodiversity [5]. The beauty of Dal Lake (Figure S1 in the Supplementary Materials) has been described and appreciated for centuries. Walter Roper Lawrence, as Resettlement Commissioner of Srinagar in 1887, wrote about the Dal Lake: "Perhaps in the whole world there is no corner as pleasant as Dal Lake". Praising the



water of Dal Lake, he mentioned "The water of the Dal is clear and soft as silk, and the people say that the shawls of Kashmir owe much of their excellence to being washed in the soft waters of the lake" [6].

Lake waters hold a well-defined part of freshwater sources, which are essential for the survival and well-being of different forms of life in an ecosystem. These serve in multidimensional activities, such as sources of drinking water, irrigation, fishery, landscape entertainment, trade, and energy production. However, these functions depend on the water quality, which needs to be kept at a certain level to maintain a well-balanced environment in terms of its physical, chemical, and biological variables. Moreover, a few elements are necessary when their concentrations are under sure cutoff points: trace metals become toxic when they exceed certain concentration limits, organic matter makes water eutrophic, and excess minerals may make water of awful quality [7]. Lamentably, in the most recent couple of decades, these characteristic freshwater assets are being contaminated because of unpredictable human intercession for the sake of advancement and urbanization [8]. The serious issue in lake wellbeing is the nutrient advancement, which invigorates the development of plants and at last prompts the decrease in water quality and the whole ecosystem [7]. Globally, the greater part of the lakes have been overwhelmed by this progression of eutrophication and as an outcome, the attributes displayed are non-consumable water, reduced fish production, undermined biodiversity, and poor flood retention limit [9]. Surface water quality in a water body is subjective to both natural and anthropogenic processes. Dumping of sewage, household squanders, use of fertilizers, and pesticides and over abuse of lake services and products in and around water bodies engenders stress on these biological systems, which changes the physical and chemical factors [10]. It has been reported that such activities have imparted huge pressure on aquatic ecosystems, resulting in a decrease in water quality and biodiversity, loss of critical habitats, and an overall decrease in quality of life for people living in the vicinity [11–13]. Hence, periodical monitoring of physicochemical parameters is imperative for the assessment of water quality.

The lake has tremendous ecological, cultural, and socio-economic importance in the region as it is a major tourist attraction in the Kashmir valley, which attracts tourists from whole world and is an important source of vegetables, fisheries, and recreation to the people of Srinagar city. Therefore, the present study was designed to assess the pollution sources, levels, and causes of spatiotemporal variations in lake water quality by determination of both similarity and differences in physicochemical attributes of water during the four seasons at four sites of Dal Lake using a multivariate technique (discriminant analysis) and arithmetic approach (water quality index).

2. Material and Methods

2.1. Study Area

This study was aimed at the assessment of physicochemical parameters of the surface waters of Dal Lake (Figure 1), which is situated in Srinagar, India, and lies between the geographical coordinates of 34°5′–34°9′ N and 74°49′–74°53′ E at an altitude of 1585above sea level. The criteria for selection of sampling sites were based on the population density and lake catchment areas. Therefore, a total of four different sites were selected; Site I (Hazratbal Dhobi Ghat), Site II (near Tailbal Nallah), Site III (near Sher-i-Kashmir International Conference Centre (SKICC)), and Site IV (near the Dal Lock-Gate). Based on the designed criteria Site I is heavily populated area, Site II is near major inlet, Site III is least populated, and Site IV is near the outlet and populated as well.



Figure 1. Map of Dal Lake showing layout of study area(Google maps).

2.2. Methodology

Surface water samples were drawn thrice from the selected sites of Dal Lake in each season for the year 2016–2017 and were analyzed for several physicochemical parameters, which include temperature, pH, alkalinity, conductivity, chlorides, total hardness, dissolved oxygen (DO), biological oxygen demand (BOD), chemical oxygen demand (COD), nitrate nitrogen, ammoniacal nitrogen, total phosphorous, and orthophosphorous. However, temperature, pH and the samples for dissolved oxygen estimation were fixed at the sampling sites at the time of sampling. The analysis was performed as per the standard methods [14–16]. In this spatiotemporal study, four different sampling sites (spatial) and four seasons (temporal) were taken into account for comparative assessment of water quality parameters.

2.3. Statistical Analysis

Discriminant analysis (DA), a multivariate statistical technique, was used to evaluate obtained datasets and illustrate conclusions regarding the similarities and dissimilarities existing amongst sampling sites and monitoring periods, as well as to identify variables specific to spatial and temporal water quality variations in Dal Lake [17].

2.4. Water Quality Index (WQI)

In this study, water quality was estimated using Brown's Water Quality Equation [18]. The water quality index (WQI) demonstrates the water quality in terms of index number and offers a valuable introduction of general water quality for open or any expected use, in addition to the pollution remediation programs and in-water quality management [19]. WQI was calculated by the following equation:

$$WQI = \Sigma qnWn / \Sigma Wn$$
 (1)

$$qn = 100(Vn - Vi)/(Vs - Vi)$$
 (2)

where, qn = quality rating; Vn = observed value; Vi = ideal value; Vs = standard permissibility limit;

$$Wn = k/Sn \tag{3}$$

$$k = [1/(\Sigma 1/Sn = 1, 2, \dots n)]$$
(4)

where, Wn = unit weight for nth parameter; Sn = standard permissible value for nth parameter; k = proportionality constant;

In this study, a total of 8 physicochemical parameters (as given in Table 1) were used as indicators for calculation of WQI. The suitability of WQI values for human consumption is rated from "excellent water" to "water unfit for use". These WQI values are prescribed in such a way that 0–25(Excellent); 26–50(Good); 51–75(Bad); 76–100(Very Bad), and above 100(Unfit). The Equations (2)–(4) were applied to various indicators and annotated values were further incorporated into Equation (1) to obtain the results [20].

Parameter	BIS/ICMR Standard (Vs)	Unit Weight (Wn)
pH	8.5	0.210471
Alkalinity	120	0.014908
Conductivity	300	0.005963
Chlorides	250	0.007156
Hardness	300	0.005963
DO	5	0.3578
BOD	5	0.3578
Nitrate-N	45	0.039756
	0.999817	

Table 1. Relative weight of parameters used for WQI calculation.

3. Results and Discussion

3.1. Physicochemical Analysis

Evaluation of physicochemical factors is basic to the understanding of the trophic status of the concerned water body. These deduced characteristics of the lake water analyzed in different seasons at different sites 2016–2017 are presented as whisker and mean plots with standard deviations in Figure 2. In present study, most of the physicochemical parameters showed a high standard deviation, which is an indication of spatiotemporal variations expectedly caused due to anthropogenic activities and climatic aspects. Water temperature, a characteristic seasonal feature, ranged from a minimum of 3 °C in winter at Site I to a maximum of 25.5 °C in summer at Site IV. pH recorded during the course of study was in alkaline range and ranged from 7.0 at Site III during autumn to 8.5 in summer at Site IV, suggesting the lake as well buffered and productive in nature [21]. Total alkalinity ranged from 110 mg/L at Site III during spring to 190 mg/L at Site IV during winter. The alkaline nature of the lake may be attributed to photosynthetic activity of primary producers [5,21]. Electrical conductivity was found to be maximum in autumn at Site IV and minimum during summer at Site II. The higher conductivity during autumn may be attributed to a higher rate of decomposition and decreasing water levels in the lake. The low values in summer may be due to higher rates of assimilation by lake biota [22]. The catchment areas of lake are rich in limestone and dolomites, the wealthy sources of calcium and magnesium ions [23]. Total hardness was maximum 378.6 mg/L at Site IV during summer and minimum 60 mg/L at Site III during autumn. Maximum water flow, precipitation of calcium carbonate, and photosynthetic activity of primary producers may be the other reasons for higher hardness during summer. Chloride concentration was minimum 18.3 mg/L at Site III during winter and maximum 43 mg/L at Site IV during summer. Higher chloride values at Sites I and IV are indicating higher anthropogenic pressures in these areas [24]. DO and water temperature are negatively related because warm water can hold less DO than cold water as the solubility of oxygen

decreases with increase in temperature [25]. DO was minimum 5.1 mg/L at Site I during summer and maximum 8.5 mg/L at Site III during winter. Maximum BOD and COD were recorded at Site I and IV during autumn and minimum at Site II in winter. Sites I and IV have higher BOD and COD, which is in accordance with previous studies and is attributed to higher loads of agricultural runoff and domestic wastewater [26]. Higher proportions of ammoniacal nitrogen, nitrate nitrogen, total phosphorous, and orthophosphorous were observed during summer and low during winter, which may be attributed to the increased pollution loads and agricultural runoff during summer [26,27].



Figure 2. Cont.



Figure 2. Whisker and mean plots showing spatiotemporal dynamics of physicochemical parameters.

Water quality monitoring and assessment is not only obliging to assess the impact of different sources of pollution but also to protect aquatic life and to establish efficient management of water

sources [28]. Temperature, pH, DO, and orthophosphate are among some physicochemical parameters that need to be monitored continuously for water quality management. The safety ranges of pH, alkalinity, DO, and ammonia nitrogen leads to health growth and avoids mortalities. Higher values of alkalinity (>100 mg/L) helps the assimilation of nitrogen by heterotrophic bacteria and nitrification process by chemoautotrophic bacteria [29]. Higher levels of total nitrogen, ammonia nitrogen, and total phosphorous are of common concern because of their ability to cause nuisance algal growth [30]. Chlorides are harmful to freshwater vegetation, and its presence in water is responsible for increased rate of corrosion [31]. The presence of enormous biodegradable organic matter in water leads to consumption of DO by bacteria and consequently drops the DO levels below the threshold point. This exhibits negative impact on aquatic life including fish as they are unable to grow and reproduce [32]. DO above 4.0 mg/L is considered good for fish, shrimp, microbiota respiration, and growth. DO concentrations exhibit an inverse relationship with BOD/COD levels. Low BOD/COD indicate good water quality, whereas high levels of BOD/COD indicate polluted water and cause harm to aquatic life [33].

This study was aimed at analysis of physicochemical parameters to evaluate the drift in physical and chemical properties of lake water in the context of anthropogenic pressure and different climatic conditions of a year as a function of water quality. However, more advanced techniques, such as geographic information system (GIS) and remote sensing technology, can be used for real-time monitoring and assessment of this resource to track the encroachments for settlement and infrastructural development as the natural population growth increases the amount of land cover by urban and agricultural development over this time period as well as the groundwater demand due to an increase in drinking water demand, urban water usage, and irrigation [34–36].

3.2. Discriminant Analysis

Stepwise DA was used to assess the spatial and temporal variations in physicochemical parameters of Dal Lake waters. On analysis, three discriminant functions (DFs) were found for each sampling site and season to discriminate between the quality of these sites and seasons. All the functions were found statistically significant (p < 0.05) by Wilks' Lambda test.

For spatial variations, the first two DFs accounted for 96.2% total variance between the four sampling sites, where the first and second DF accounted for 82.5% and 13.7% of total spatial variance, respectively. The factors temperature, alkalinity, ammoniacal nitrogen, total phosphorous, and orthophosphorous exhibited a strong contribution in first group (DF1) followed by BOD and nitrate in second group (DF2) and putative for the majority of expected temporal variations in lake, while the remaining parameters exhibited a relatively weak contribution in discrimination of four sampling sites. The relative contribution of each parameter in each DF is given in Table 2. Canonical discriminant plot for spatial variations (Figure 3a) elucidated that DF1 best discriminates Sites III and IV than Sites I and II, while the y-axis shows that DF2 best discriminates Sites I from IV than Sites II and III. Site IV followed by Site I exhibited positive loadings for DF1 factors, which implies that these sites were characterized by elevated levels of temperature, alkalinity, ammoniacal nitrogen, total phosphorous, and orthophosphorous, however Sites II and III exhibited a negative association with these factors. For DF2 factors, Site IV exhibited positive loadings followed by Site II, which implies that these sites were characterized by elevated levels of BOD and nitrate nitrogen whereas, Sites I and III exhibited negative association with these factors. The high loading values for these parameters may be directly attributed to higher anthropogenic pressures and agricultural runoff, sewage, and waste disposal because of a high human population living in these hamlets (Sites I and IV).

For temporal variations, the first two DFs accounted for 97% total variance between the four sampling seasons, where the first and second DF accounted for 85.8% and 11.3% of total variance, respectively. Temperature, alkalinity, hardness, BOD, nitrate nitrogen, and total phosphorous exhibited a strong contribution in first group (DF1) followed by DO in second group (DF2) and putative for majority of expected temporal variations in lake, while remaining parameters exhibited a relatively

_

weak contribution in discrimination of four sampling seasons. The relative contribution of each parameter in each DF is given in Table 3. A canonical discriminant plot for temporal variations (Figure 3b) elucidated that DF1 best discriminated summer and winter than spring and autumn, which lie close to each other. Summer exhibited positive loadings for DF1 factors, which indicate that summer was characterized by elevated levels of temperature, alkalinity, hardness, BOD, and nitrate nitrogen, whereas winter exhibited strong negative association with these factors. For DF2 factors, spring and autumn exhibited positive loadings with less difference, which implies that these sites were characterized by elevated levels of DO, whereas summer exhibited a negative association with DO. These temporal variations may be attributed to increasing volumes of inlet waters from spring to summer and higher anthropogenic pressures during summer.

Standardized Canonical Discriminant Function Coefficients										
		Functions								
	1	2	3							
Water Temperature	-3.031	1.188	5.123							
pH	1.725	2.490	0.832							
Alkalinity	2.421	0.947	1.737							
Hardness	-0.696	0.891	-1.135							
Chlorides	-1.813	0.241	-0.512							
BOD	-0.267	-1.107	-0.052							
Nitrate	-0.977	1.179	-3.231							
Ammonia	2.162	-0.046	-0.834							
Total Phosphorous	2.478	1.214	-0.196							
Orthophosphorous	3.615	-4.431	0.433							
	Eigenvalues									
Eigenvalue	50.181	8.360	2.282							
% of Variance	82.5	13.7	3.8							
Cumulative%	82.5	96.2	100.0							
Canonical Correlation	0.990	0.945	0.834							
	Wilks' Lambda									
Wilks' Lambda	0.001	0.033	0.305							
Chi-square	294.411	136.997	47.539							
DÎ	30	18	8							
Sig.	0.000	0.000	0.000							

Table 2. Summary of canonical discriminant functions for spatial variations in lake water.



Figure 3. Canonical discriminant plot showing (a) spatial variation and (b) temporal variation of physicochemical parameters of Dal Lake water.

Standardized Canonical Discriminant Function Coefficients										
		Functions								
	1	2	3							
Water Temperature	2.406	0.526	0.544							
Alkalinity	-2.589	0.537	0.553							
Conductivity	0.319	0.844	0.126							
Hardness	-2.135	-1.385	0.728							
DO	-0.172	1.374	1.028							
BOD	1.643	0.467	0.132							
Nitrate	3.164	0.328	0.089							
Total Phosphorous	-0.916	0.857	-1.077							
*	Eigenvalues									
Eigenvalue	391.282	51.633	13.136							
% of Variance	85.8	11.3	2.9							
Cumulative%	85.8	97.1	100.0							
Canonical Correlation	0.999	0.990	0.964							
	Wilks' Lambda									
Wilks' Lambda	0.000	0.001	0.071							
Chi-square	515.946	271.095	108.598							
Dŕ	24	14	6							
Sig.	0.000	0.000	0.000							

Table 3. Summary of canonical discriminant functions for temporal variations in lake water.

3.3. Water Quality Index

Calculation of WQI by weighted arithmetic index method initiates with the estimation of unit weight (Wn) for each physicochemical parameter used in the calculation of WQI. Water quality standards and the assigned unit weights for each physicochemical parameter used for WQI calculation are given in Table 1. On the basis of Wn, DO and BOD were of highest significance, as these were assigned a maximum weight of 0.3578 each. WQI was calculated for each season at each site and is given in Tables 4–7.

Demonstern	Spring			Summer			Autumn			Winter		
Parameter –	Vn	Qn	QnWn	Vn	Qn	QnWn	Vn	Qn	QnWn	Vn	Qn	QnWn
pН	7.77	51.33333	10.80416	7.73	48.66667	10.2429	7.36	24	5.051294	7.23	15.33333	3.227216
Alkalinity	122.3	101.9167	1.519408	132	110	1.639917	130.3	108.5833	1.618797	151.67	126.3917	1.884289
Conductivity	204	27.2	0.064881	176.3	58.76667	0.350445	284.3	94.76667	0.565125	238.67	79.55667	0.474423
Chlorides	30.7	12.28	0.087876	36.7	14.68	0.10505	31	12.4	0.088734	22.67	9.068	0.064891
Hardness	130.7	43.56667	0.259803	326.6	108.8667	0.649208	86.3	28.76667	0.171545	201	67	0.399543
DO	8.6	62.5	22.3625	5.13	98.64583	35.29548	5.96	90	32.202	8.13	67.39583	24.11423
BOD	12.5	250	89.45	21.5	430	153.854	24.3	486	173.8908	10.16	203.2	72.70496
Nitrate-N	1.38	3.066667	0.121917	1.43	3.177778	0.126334	1.23	2.733333	0.108665	0.919	2.042222	0.08119
	ΣWnQn		124.6705	ΣW	/nQn	202.2633	ΣW	/nQn	213.697	ΣW	'nQn	102.9507
	WQI		125.1412	V	/QI	202.3003	W	VQI	213.736	И	/QI	102.9696
	Average WQI = 161											

 Table 4. Calculation of WQI at Site I.

 Table 5. Calculation of WQI at Site II.

Devenuetov	Spring			Summer			Autumn			Winter		
r araineter –	Vn	Qn	QnWn	Vn	Qn	QnWn	Vn	Qn	QnWn	Vn	Qn	QnWn
pН	7.57	38	7.997882	7.63	42	8.839765	7.2	13.33333	2.806275	7.43	28.66667	6.03349
Alkalinity	130.3	108.5833	1.618797	125.67	104.725	1.561275	141.67	118.0583	1.760053	120.3	100.25	1.49456
Conductivity	264.3	35.24	0.084059	140.3	46.76667	0.278885	289.67	96.55667	0.5758	281.3	93.76667	0.559162
Chlorides	28.3	11.32	0.081006	31	12.4	0.088734	29	11.6	0.08301	20	8	0.057248
Hardness	143.3	47.76667	0.284849	255	85	0.506883	63	21	0.12523	162.3	54.1	0.322616
DO	8.07	68.02083	24.33785	11	37.5	13.4175	6.6	83.33333	29.81667	8.27	65.9375	23.59244
BOD	8	160	57.248	21.6	432	154.5696	14.5	290	103.762	6.5	130	46.514
Nitrate-N	1.57	3.488889	0.138703	1.63	3.622222	0.144003	1.43	3.177778	0.126334	0.737	1.637778	0.065111
	ΣWnQn		91.79115	ΣWnOn		179.4066	ΣWnOn		139.0554	ΣWnOn		78.63863
	WQI		92.13767	W	/QI	179.4395	М	/QI	139.0808	W	/QI	78.65301
	Average WQI =122											

Deverseter	Spring			Summer			Autumn			Winter		
Parameter –	Vn	Qn	QnWn	Vn	Qn	QnWn	Vn	Qn	QnWn	Vn	Qn	QnWn
pН	7.83	55.33333	11.64604	8.07	71.33333	15.01357	7.06	4	0.841882	7.03	2	0.420941
Alkalinity	110	91.66667	1.366597	101.3	84.41667	1.258512	125	104.1667	1.552951	161.3	134.4167	2.003928
Conductivity	236	31.46667	0.075058	166.3	55.43333	0.330567	297.67	99.22333	0.591702	248.3	82.76667	0.493565
Chlorides	23.67	9.468	0.067753	28.3	11.32	0.081006	24.67	9.868	0.070615	18.3	7.32	0.052382
Hardness	119.67	39.89	0.237877	239.67	79.89	0.476411	60.66	20.22	0.120579	119.3	39.76667	0.237142
DO	8.5	63.54167	22.73521	5.4	95.83333	34.28917	6.4	85.41667	30.56208	8	68.75	24.59875
BOD	8	160	57.248	11.27	225.4	80.64812	13.3	266	95.1748	7.6	152	54.3856
Nitrate-N	1.318	2.928889	0.11644	1.35	3	0.119267	1.27	2.822222	0.112199	0.79	1.755556	0.069793
	ΣWnQn		93.49297	ΣW	'nQn	132.2166	ΣW	/nQn	129.0268	ΣW	/nQn	82.2621
	WQI		93.84591	И	/QI	132.2408	М	/QI	129.0504	V	VQI	82.27715
	Average WQI =109											

Table 6. Calculation of WQI at Site III.

Table 7. Calculation of WQI at Site IV.

Parameter –	Spring			Summer			Autumn			Winter		
	Vn	Qn	QnWn	Vn	Qn	QnWn	Vn	Qn	QnWn	Vn	Qn	QnWn
pН	8.1	73.33333	15.43451	8.53	102	21.468	7.47	31.33333	6.594745	7.47	31.33333	6.594745
Alkalinity	140.3	116.9167	1.743033	130.3	108.5833	1.618797	169	140.8333	2.09959	190.67	158.8917	2.36881
Conductivity	221.67	29.556	0.070501	121.3	40.43333	0.241117	318	106	0.632113	233.3	77.76667	0.463749
Chlorides	27.3	10.92	0.078144	43	17.2	0.123083	35.3	14.12	0.101043	28.3	11.32	0.081006
Hardness	167.83	55.94333	0.333609	378.67	126.2233	0.752712	80.3	26.76667	0.159619	191.3	63.76667	0.380262
DO	7.77	71.14583	25.45598	5.6	93.75	33.54375	5.47	95.10417	34.02827	7.53	73.64583	26.35048
BOD	13	260	93.028	14	280	100.184	18.5	370	132.386	13	260	93.028
Nitrate-N	1.54	3.422222	0.136052	1.62	3.6	0.14312	1.35	3	0.119267	0.97	2.155556	0.085695
	ΣWnQn		136.2798	ΣW	'nQn	158.0746	ΣW	VnQn	176.1206	ΣW	'nQn	129.3527
	WQI		136.7943	И	/QI	158.1035	V	VQI	176.1529	М	/QI	129.3764
	Average WQI =150											

The WQI values elucidated that the water of Dal Lake is excessively polluted and unfit for human consumption. The average WQI for Site I, Site II, Site III, and Site IV are 161, 122, 109, and 150 respectively, demonstrating that the maximum deteriorated water quality was observed at Site I—a highly populated area—and least at Site III—the least populated area—thus suggesting that anthropogenic pressures are the main reason behind the deterioration of water quality of Dal Lake. Spatiotemporally, Site I was observed as the most contaminated during autumn followed by summer.

4. Conclusions

The main focus of this study was to evaluate spatiotemporal variations in the surface water quality of Dal Lake using statistical and arithmetic exploratory techniques to ascertain pollution sources. The results of these methods exhibited that the variation in water quality of the lake is more subjected to anthropogenic pressures than change in the climatic conditions. The discriminant analysis separated sampling sites and seasons in a simpler, illustrative manner and highlighted the contribution of each physicochemical parameter. The water quality index is helpful in assessment and management of water quality. Based on obtained WQI values, this study provides necessary understanding into the status of overall suitability of the Dal Lake water. The WQI helped in the transformation of complex datasets into a numeric expression and presented the status of water quality as a single number, which elucidates that indiscriminate anthropogenic pressures by (population loads) are pushing the lake ecosystem towards an unnatural death. Thus, as a result of this study, it can be concluded that the lake is moving towards its definite end. For restoration of this aesthetic asset and biologically diverse natural habitat, effective treatment measures are urgently required; encroachments for settlement and infrastructural development must be banned and existing ones should be removed, in addition to regulation of sewage and waste disposal into the lake to conserve this ecosystem of high socio-economic importance.

The overall water quality was evaluated using WQI, which has some limitations, so it may not convey enough information about the actual situation of the Lake, but in the future, this study can be used as a case study to strengthen the research findings related to Dal Lake water quality management. Our results can be helpful to decision makers to elucidate priorities in pollution prevention efforts and management of the lake. Besides this, geographic information system (GIS) and remote sensing technology can be further employed for real-time monitoring and assessment of this resource as urbanization is forcing the lake to shrink.

Supplementary Materials: The following are available online at http://www.mdpi.com/2073-4441/12/9/2365/s1, Figure S1: Dal Lake.

Author Contributions: Conceptualization, T.A., G.G., B.K. and P.A.; methodology, T.A., G.G. and A.S.; software, A.A.A.; validation, G.G., A.S. and B.K.; formal analysis, P.A.; investigation, T.A.; resources, B.K.; data curation, B.K. and P.A.; writing—original draft preparation, T.A., G.G., A.S. and B.K.; writing—review and editing, B.K., A.A.A. and P.A.; visualization, G.G.; supervision, B.K.; project administration, B.K.; funding acquisition, A.A.A. and P.A. All authors have read and agreed to the published version of the manuscript.

Acknowledgments: The authors would like to extend their sincere appreciation to the Researchers Supporting Project Number (RSP-2020/236), King Saud University, Riyadh, Saudi Arabia.

Conflicts of Interest: The authors declare no conflict of interest.

References

- Zutshi, D.; Vass, K. Limnological Studies on Dal Lake, Srinagar. III. Biological Features. Proc. Indian Natl. Sci. Sect. B 1982, 48, 234–241.
- 2. Ul Solim, S.; Wanganeo, A. Excessive phosphorus loading to Dal Lake, India: Implications for managing shallow eutrophic lakes in urbanized watersheds. *Int. Rev. Hydrobiol.* **2008**, *93*, 148–166. [CrossRef]
- 3. Micklin, P. The Aral sea disaster. Annu. Rev. Earth Planet. Sci. 2007, 35, 47–72. [CrossRef]
- Hussein, H. Politics of the Dead Sea Canal: A historical review of the evolving discourses, interests, and plans. Water Int. 2017, 42, 527–542. [CrossRef]

- 5. Qadri, H.; Yousuf, A. Dal Lake ecosystem: Conservation strategies and problems. In Proceedings of the TAAL 2007: The 12th World Lake Conference, Jaipur, India, 28 October–2 November 2007; pp. 1453–1457.
- 6. Lawrence, W.R. The Valley of Kashmir; H. Frowde: London, UK, 1895.
- 7. Yu, F.C.; Fang, G.H.; Ru, X.W. Eutrophication, health risk assessment and spatial analysis of water quality in Gucheng Lake, China. *Environ. Earth Sci.* **2010**, *59*, 1741–1748. [CrossRef]
- 8. Bora, M.; Goswami, D.C. Water quality assessment in terms of water quality index (WQI): Case study of the Kolong River, Assam, India. *Appl. Water Sci.* **2016**, *7*, 3125–3135. [CrossRef]
- 9. Fink, G.; Alcamo, J.; Flörke, M.; Reder, K. Phosphorus loadings to the world's largest lakes: Sources and trends. *Glob. Biogeochem. Cycles* **2018**, *32*, 617–634. [CrossRef]
- 10. Zhao, Y.; Xia, X.H.; Yang, Z.F.; Wang, F. Assessment of water quality in Baiyangdian Lake using multivariate statistical techniques. *Procedia Environ. Sci.* **2012**, *13*, 1213–1226. [CrossRef]
- 11. Niemi, G.J.; DeVore, P.; Detenbeck, N.; Taylor, D.; Lima, A.; Pastor, J.; Yount, J.D.; Naiman, R.J. Overview of case studies on recovery of aquatic systems from disturbance. *Environ. Manag.* **1990**, *14*, 571–587. [CrossRef]
- Kazi, T.; Arain, M.; Jamali, M.K.; Jalbani, N.; Afridi, H.; Sarfraz, R.; Baig, J.; Shah, A.Q. Assessment of water quality of polluted lake using multivariate statistical techniques: A case study. *Ecotoxicol. Environ. Saf.* 2009, 72, 301–309. [CrossRef]
- Herrera-Silveira, J.A.; Morales-Ojeda, S.M. Evaluation of the health status of a coastal ecosystem in southeast Mexico: Assessment of water quality, phytoplankton and submerged aquatic vegetation. *Mar. Pollut. Bull.* 2009, 59, 72–86. [CrossRef] [PubMed]
- Eaton, A.D.; Clesceri, L.S.; Rice, E.W.; Greenberg, A.E.; Franson, M. Standard Methods for the Examination of Water and Wastewater, 21st ed.; American Public Health Association, American Waterworks Association, Water Environmental Federation: Washington, DC, USA, 2005; pp. 1–88.
- 15. Trivedy, R.; Goel, P. *Chemical and Biological Methods for Water Pollution Studies*; Environmental Publications: Portland, OR, USA, 1984.
- 16. US-EPA. *Methods for Chemical Analysis of Water and Wastes;* Environmental Protection Agency: Washington, DC, USA, 1991.
- Singh, K.P.; Malik, A.; Mohan, D.; Sinha, S. Multivariate statistical techniques for the evaluation of spatial and temporal variations in water quality of Gomti River (India)—A case study. *Water Res.* 2004, *38*, 3980–3992. [CrossRef] [PubMed]
- Brown, R.M.; McClelland, N.I.; Deininger, R.; Tozer, R.G. A water quality index-do we dare? water sewage works. *Ojahio Mcred* 1970, 117, 339–343.
- 19. Bhat, S.A.; Pandit, A.K. Surface Water Quality Assessment of Wular Lake, A Ramsar Site in Kashmir Himalaya, Using Discriminant Analysis and WQI. *J. Ecosyst.* **2014**, 2014, 1–18. [CrossRef]
- Brown, R.M.; McClelland, N.I.; Deininger, R.A.; O'Connor, M.F. A Water Quality Index—Crashing the Psychological Barrier. In *Indicators of Environmental Quality*; Springer: New York, NY, USA, 1972; pp. 173–182. [CrossRef]
- 21. Garg, R.; Rao, R.; Uchchariya, D.; Shukla, G.; Saksena, D. Seasonal variations in water quality and major threats to Ramsagar reservoir, India. *Afr. J. Environ. Sci. Technol.* **2010**, *4*, 61–76.
- Lu, Q.; He, Z.L.; Graetz, D.A.; Stoffella, P.J.; Yang, X. Phytoremediation to remove nutrients and improve eutrophic stormwaters using water lettuce (Pistia stratiotes L.). *Environ. Sci. Pollut. Res.* 2010, 17, 84–96. [CrossRef]
- 23. Jeelani, G.; Shah, A.Q. Geochemical characteristics of water and sediment from the Dal Lake, Kashmir Himalaya: Constraints on weathering and anthropogenic activity. *Environ. Geol.* 2006, *50*, 12–23. [CrossRef]
- 24. Rashid, I.; Romshoo, S.A.; Amin, M.; Khanday, S.A.; Chauhan, P. Linking human-biophysical interactions with the trophic status of Dal Lake, Kashmir Himalaya, India. *Limnologica* **2017**, *62*, 84–96. [CrossRef]
- 25. Solanki, V.R.; Hussain, M.M.; Raja, S.S. Water quality assessment of Lake Pandu Bodhan, Andhra Pradesh State, India. *Environ. Monit. Assess.* **2010**, *163*, 411–419. [CrossRef]
- 26. Najar, I.A.; Khan, A.B. Assessment of seasonal variation in water quality of Dal Lake (Kashmir, India) using multivariate statistical techniques. In Proceedings of the Water Pollution XI, Southampton, UK, 10 July 2012.
- 27. Khan, M.Y.A.; Hu, H.; Tian, F.; Wen, J. Monitoring the spatio-temporal impact of small tributaries on the hydrochemical characteristics of Ramganga River, Ganges Basin, India. *Int. J. River Basin Manag.* 2020, *18*, 231–241. [CrossRef]

- 28. Varol, M.; Gökot, B.; Bekleyen, A.; Şen, B. Spatial and temporal variations in surface water quality of the dam reservoirs in the Tigris River basin, Turkey. *Catena* **2012**, *92*, 11–21. [CrossRef]
- Emerenciano, M.G.C.; Martínez-Córdova, L.R.; Martínez-Porchas, M.; Miranda-Baeza, A. Biofloc technology (BFT): A tool for water quality management in aquaculture. In *Water Quality*; Tutu, H., Ed.; IntechOpen: Rijeka, Croatia, 2017; pp. 92–109.
- 30. Sharip, Z.; Suratman, S. Formulating specific water quality criteria for lakes: A Malaysian perspective. In *Water Quality;* Tutu, H., Ed.; IntechOpen: Rijeka, Croatia, 2017; pp. 293–313.
- Ruman, M.; Polkowska, Ż.; Zygmunt, B. Processes and the Resulting Water Quality in the Medium-Size Turawa Storage Reservoir after 60-Year Usage. In *Water Quality*; Tutu, H., Ed.; IntechOpen: Rijeka, Croatia, 2017; pp. 377–400.
- 32. Igbinosa, E.; Okoh, A. Impact of discharge wastewater effluents on the physico-chemical qualities of a receiving watershed in a typical rural community. *Int. J. Environ. Sci. Technol.* **2009**, *6*, 175–182. [CrossRef]
- 33. Edokpayi, J.N.; Odiyo, J.O.; Durowoju, O.S. Impact of wastewater on surface water quality in developing countries: A case study of South Africa. In *Water Quality*; Tutu, H., Ed.; IntechOpen: Rijeka, Croatia, 2017; pp. 401–416.
- Mohammad, A.H.; Jung, H.C.; Odeh, T.; Bhuiyan, C.; Hussein, H. Understanding the impact of droughts in the Yarmouk Basin, Jordan: Monitoring droughts through meteorological and hydrological drought indices. *Arab. J. Geosci.* 2018, *11*, 103. [CrossRef]
- 35. Odeh, T.; Mohammad, A.H.; Hussein, H.; Ismail, M.; Almomani, T. Over-pumping of groundwater in Irbid governorate, northern Jordan: A conceptual model to analyze the effects of urbanization and agricultural activities on groundwater levels and salinity. *Environ. Earth Sci.* **2019**, *78*, 40. [CrossRef]
- Riad, P.; Graefe, S.; Hussein, H.; Buerkert, A. Landscape transformation processes in two large and two small cities in Egypt and Jordan over the last five decades using remote sensing data. *Landsc. Urban.Plan.* 2020, 197, 103766. [CrossRef]



© 2020 by the authors. Licensee MDPI, Basel, Switzerland. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license (http://creativecommons.org/licenses/by/4.0/).